



Maintaining the optimal performance of your jets is crucial for ensuring a refreshing experience in your pool or spa. Here's a comprehensive guide to unblocking your jets efficiently:

Tools Required:

22mm socket (available at Bunnings or Total Tools)
Screwdriver or any tool with a pointy or slim tip



22mm socket

Procedure:

Remove the Eyeball: Begin by gently removing the eyeball from your pool. Use a screwdriver to carefully pry off any adhesive securing it in place.

Unlock the Nozzle: Utilize the 22mm socket to twist the nozzle anti-clockwise, loosening it from its position.

Extract the Nozzle: With the nozzle unlocked, carefully pull it out of its housing. Take note to handle it delicately to avoid any damage.

Thorough Cleaning: Inspect the removed nozzle for any obstructions or debris. Clean it meticulously to ensure the entire pathway is clear, enabling optimal water flow.

Reassemble: Once cleaned, securely place the nozzle back into its housing. Use the 22mm socket to twist it clockwise, firmly locking it in position.

Restore the Eyeball: Place the white eyeball back into its designated spot, ensuring it is snugly fitted.

Test Run: With everything reassembled, activate your pool equipment and observe the jets working at full pressure.

Important Note:

*Regular maintenance of your jets is crucial to prevent blockages and ensure optimal performance.

*Remember, issues with jets typically stem from maintenance rather than warranty concerns.

*By keeping your jets clean and well-maintained, you can consistently enjoy the rejuvenating experience they provide.

Follow these steps diligently to keep your pool jets functioning flawlessly, providing you with endless relaxation and enjoyment.

VIDEO